

AntTec Group Co,Ltd

Aluminum Surface Infrared Panel Heater



Technical Details

Controls	<ul style="list-style-type: none"> Digitally controlled electronic thermostat(5-40°C) Clear LCD display 433 wireless remote control App control weekly program open window detection
Construction	<ul style="list-style-type: none"> All aluminum construction innovation design, no frame
Element	<ul style="list-style-type: none"> Long life carbon crystal heating element 4 tiers PET, total 0.8mm thickness
Installation	Strong mounting brackets for easy fixing
Safe	<ul style="list-style-type: none"> thermal cut-out ,auto reset type overheat detection
IP rating	IP24
Supply	<ul style="list-style-type: none"> 1.8 metre fitted; 3X1.0H05RN-F Class 1 ,with earth wire!
Colour/finish	White

Warranty & Approvals

Approvals	CE UKCA ROHS
Warranty	2 Years


Product Description

Infrared heaters are more energy-efficient than other space heaters as they do not heat up the entire room. Convection heaters heat the air and air circulation can cause a significant loss of heat. As soon as doors are opened or briefly ventilated, the room temperature drops. Infrared heaters instead heat matter, such as people, furniture and walls. These then release heat back into the room over time. With an infrared heater you do not have to heat the entire room, but can create heated zones and direct the heat to specific areas while allowing the air to remain cool and fresh.

Key Features

- Five panel heater outputs 300W,350W,500W,700W,900W.
- Contracted design, Clear LCD display
- 433 wireless remote control
- APP control power by TUYA.
- Long life Carbon crystal heating element
- Energy efficient low energy costs,electric conversion efficiency 98%
- Draught and Noise free
- Can be Ceiling ,Wall Mounted or free stand.
- IP24 Protection

Details&Dimensions



Install style



Mounting bracket



Control panel

Model	ACB30	ACB35	ACB52	ACB70	ACB90
Power (w)	300	350	520	700	900
Long(CM)	50	60	90	120	120
Width(CM)	4.5	4.5	4.5	4.5	4.5
High(CM)	60	60	60	60	80
Weight(kg)	3	4	5	8	10

Packaging details

Long(CM)	60	70	100	130	130
Width(CM)	7	7	7	7	7
High(CM)	70	70	70	70	90
Weight(kg)	4	5	6	9	11
Container loading(20)	880	750	530	400	320
Container loading(40)	1900	1600	1150	880	680
Container loading(40HQ)	2250	1900	1350	1050	800